

## HPTM890 Combined Pressure & Temperature Transmitter



Nanjing Hangjia Electronic Technology Co.,Ltd.

## Overview


HPTM890 digital display temperature and pressure transmitter integrates a highly stable pressure-sensitive element and a high-precision temperature-sensitive element for independent measurement, enabling simultaneous and accurate measurement of medium pressure and temperature. It can output two standard 4-20mA signals. Additionally, this product features a 4-digit dual-row LED field display that can simultaneously show pressure and temperature values.

Having undergone long-term aging and stability testing, the product boasts reliable and stable performance, making it suitable for harsh environments. It can accurately measure multiple parameters at a single measurement point and is widely used in industrial process control for the simultaneous measurement of fluid pressure and temperature.

## Features

- ◆ Parallel measurement of pressure and temperature
- ◆ Temperature sensor is placed close to the medium being measured, smaller measurement errors.
- ◆ Supports temperature probe
- ◆ Large LED display showing both pressure and temperature simultaneously

## Measuring principle




The temperature sensor is a built-in high-precision PT100 or PT1000. The measurement position is close to the medium to be measured, with a small temperature difference and a fast response. Temperature measurement also supports a probe structure to penetrate the center of the temperature to be measured. The pressure measurement channel uses a high-stability and high-precision silicon piezoresistive pressure sensing core. The process pressure acts directly on the isolation diaphragm, causing the diaphragm to deform. The signal conditioning circuit converts the MEMS chip signal into a standard current or voltage signal output.

## Parameters

<b>Pressure Range</b>	-100kPa...0~50kPa...40MPa (Gauge) 0~50kPa...40MPa (Absolute)
<b>Overload Pressure</b>	1.5 times full scale
<b>Temperature Range</b>	-40~100°C Note: Supports customized intermediate range, such as 0~80°C, etc.
<b>Measuring Medium</b>	Various liquids, gases and various compatible with contact materials
<b>Output Signal/Power Supply</b>	Pressure: 4~20mA <sub>DC</sub> Temperature: 4~20mA <sub>DC</sub> V <sub>S</sub> =24 V <sub>DC</sub> (9~30V <sub>DC</sub> )
<b>Accuracy</b>	Pressure: ±0.5%FS standard.; ±0.2%FS optional Temperature: ±0.4°C
<b>Compensation temperature (for pressure measure)</b>	-10~70°C
<b>Zero-point Temperature Coefficient (for pressure measure)</b>	±1.5%FS reference 30°C, within temperature compensation range
<b>Full scale Temperature Coefficient (for pressure measure)</b>	±1.5%FS reference 30°C, within temperature compensation range
<b>Medium Temperature</b>	-40~100°C
<b>Temperature Resistance of LED</b>	-30~70°C
<b>Storage Temperature</b>	-30~70°C
<b>Protection grade</b>	IP65
<b>Electric protection</b>	Reverse polarity protection
<b>Mechanical Stability</b>	Vibration 20g(20~5000Hz) Shock resistance 20g(11ms)
<b>Insulation resistance</b>	>100MΩ 500VDC
<b>Dielectric strength</b>	500VAC 50Hz test voltage applied for 1min without breakdown and arcing

**Structural Drawings (Unit: mm)**




Note:

1. The dimensions listed in the figure may change with the update of the process
2. Support customized appearance structure with temperature probe

**Structural Materials**

Ordering code	Part	Material
A12	Protection shell	Cast aluminum alloy ADC12 (default)
S4	Pressure port	SS304(default)
S6		SS316L
M1	Pressure sensor	SS316L(default)
FK	O-ring	FKM Fluor rubber sealing rings (applicable temperature range -20~200°C) (default)

### Electrical Connections



Output signal	Pressure: 4~20mADC Temperature: 4~20mADC		
Signal Definition	Power+ (+V)	Power-(0V/+OUT <sub>Pressure</sub> )	Power-(0V/+OUT <sub>Temperature</sub> )
Terminals	24VDC+	24VDC-	TEST+

## Ordering Guide

Model Name	Type							
HPM86	Combined Pressure & Temperature Transmitter							
	<b>Pressure Range</b>	<b>Pressure measuring range</b>						
	(0-X)kPa	X is upper limit of the range						
	<b>Temperature Range</b>	<b>Pressure measuring range</b>						
	(T1 ~ T2)°C	T1 is the lower limit of the range T2 is the upper limit of the range						
		<b>Code</b>	<b>Output Signal</b>					
		B1B1	Pressure: 4~20mADC Temperature: 4~20mADC					
		<b>Code</b>	<b>Process connection</b>					
		P1	M20x1.5					
		G12	G1/2					
			<b>Code</b>	<b>Electrical connection</b>				
			C7	M20x1.5 female thread, with gland				
			<b>Code</b>	<b>Pressure interface</b>				
			S6	SS316L				
				<b>Code</b>	<b>Pressure interface material</b>			
				L	L = insertion depth			
					<b>Code</b>	<b>Additional functions</b>		
					G	Gauge pressure (Default)		
					A	Absolute pressure		
					QF	Factory report		
						Other requirements		
Eg: HPM86	(0 ~ 100)kPa	(0 ~ 100)°C	B1B1	P1	C7	S4	L=0	G QF

## Certification Information

Factory certification	
Certification organization	CQM
Quality management system	ISO 9001:2015
Certification scope	Research, development and manufacture of pressure transmitter and temperature transmitter
Certificate No.	00223Q21711R1S

CE	
Certification organization	ECM
Certification scope	Pressure Transmitter
Standard	EN61326-1:2013
	EN61326-2-3:2013
	EN61000-6-2:2005/AC:2005
	EN61000-6-4:2007+A1:2011
Certificate No.	3Z200408.NHET098